

Ronco Item No : **69-570-XX (06, 07, 08, 09, 10, 11)**

Brand Name :

PRIMACUT 69-570



Description :

**TRI-POLYMER NITRILE PALM COATED
CUT-RESISTANT GLOVE - CUT LEVEL 5**

HPPE (High Performance Polyethylene) Red Liner
With Heavy Duty Abrasion-Resistant Black Tri-Polymer Nitrile Coating
And Thumb Index Reinforcement **TIR™**

Mechanical Ratings :

CE EN388 - 4542 (abrasion, cut, tear, puncture)
ANSI: ≥ Cut 4



Specifications :

Ronco Item#	69-570-06	69-570-07	69-570-08	69-570-09	69-570-10	69-570-11
Sizing	6 / XS	7 / S	8 / M	9 / L	10 / XL	11 / XXL
Width: +/- 5 (mm)	80	85	90	95	100	105
Length: +/- 5 (mm)	230	245	255	265	275	285
Overlock Serging Colour	White	Green	Grey	Yellow	Brown	Blue

Packaging :

6 pairs x 8 bags = 48 pairs per case

Applications :

PrimaCut™ 69-570 is a one-of-a-kind heavy duty cut-resistant glove designed for high cut and scrape hazards. Its advanced tri-polymer palm coating stands alone in terms of its superior level of abrasion resistance. As well, it has an excellent dry, oil and wet grip. For extra protection and durability, the glove comes equipped with a cut-resistant Thumb Index Reinforcement. Applications include:

- Steel and sheet metal fabrication and handling
- Automobile assembly
- Wire and cable handling
- Glass handling
- Construction and construction carpentry
- General handling of sharp and abrasive objects and surfaces



Product Features :

- Excellent heavy duty cut resistance level (EN 388 cut level 5)
- Cutting edge tri-polymer palm and finger coating for tough protection against abrasive surfaces
- Seamless, flexible and soft cut-resistant liner for a more comfortable and cool feel
- Cut-resistant thumb Index reinforcement for extra protection and durability
- Elasticized knit wrist with different serging colour for easy size identification
- Machine washable and re-usable for cost-efficiency

Storage & Handling :

Store at room temperature under roof away from direct sunlight and moisture. Machine wash in cool or warm water. Tumble dry at the lowest temperature setting or hang to dry.

Special Notes :

While this product is cut-resistant, it is not cut proof. Its use is not recommended with moving or serrated blades.

Although reasonable care has been taken in the preparation of this document, no warranties are extended and no liability is assumed. The information is solely provided as a general guideline for product use and care. It is up to end-users to make their own determination as to the suitability of the product for their own intended purposes.